



Front View



Rear View



## Features

- Intel® Atom™ J1900/ N2807 Processor
- DDR3L 1333 SODIMM x 2, Up to 16GB (J1900), DDR3L 1333 SODIMM x 1, Up to 4GB (N2807)
- Dual Independent Display: VGA + HDMI
- Rich IO Supported: USB 3.0 x 1, USB 2.0 x 4~7
- Compact Size, Low Power & Fanless Solution




## Specifications

System		
CPU	Intel® Atom™ J1900 Processor (4C @ 2.00 GHz CPU, 688/854 MHz GFX, 10W TDP), Intel® Atom™ N2807 Processor (2C @ 1.58 GHz CPU, 313/750 MHz GFX, 4.3W TDP)	
Chipset	—	
System Memory	204-pin SODIMM x 2 up to 8 GB (for J1900) 204-pin SODIMM x 1 up to 4 GB (for N2807) DDR3L 1333 MHz, Non-ECC, un-buffered memory, Dual-channel memory architecture	
I/O Chipset	Fintech 81866D	
Display Interface	Chipset Intel® Graphics Media Accelerator DP VGA x 1, Up to 1920 x 1200 @60 Hz ; HDMI x 1, Up to 1920 x 1200 @60 Hz	
Storage Devices	2.5" HDD, Full-Size Mini-Card (optional)	
Network	LAN Realtek PCIe Gb LAN 8111G x 1	
I/O		
Front I/O	USB	USB 2.0 port x 4
	Audio	—
	Display	VGA x 1
	Others	On/Off Button x 1, Power LED + HD LED x 1, (COM port optional if not use VGA port)
Rear I/O	USB	USB 3.0/2.0 port x 1, USB 2.0 port x 2
	Audio	Line-out (green) x 1, Line-in (blue) x 1
	Display	HDMI x 1
	LAN	RJ-45 connector x 1
	Power	DC Power x 1
Others	RS-232 connector x 1	
Expansion	Mini PCIe	Full-size Mini- Card (PCIe +USB or mSATA) + SIM Card (mSATA default) x 1, Half-size Mini-Card (PCIe +USB) x 1
	Storage	Full-size Mini-Card slot (mSATA default) x 1, SATA3 (6.0Gb/s) x 2, SATA2 (3.0Gb/s) x 2, SATA power connector x 1
	Others	RS-232 9-pin int. box header x 5, RS-232/422/485 9-pin box header x 1, 5-pin USB 2.0 header(p=2.00mm) x 1, 8-bit Digital I/O x 1 (In/Out programmable)
Indicator	Front	Power LED x 1, HDD Active LED x 1
	Rear	—
Power		
Battery	Lithium battery	
Power Requirement	DC: 12V	
Mechanical		
Dimension (WxHxD)	8" x 8" x 1.75" (203.20mm x 203.20mm x 44.45mm)	
VESA Mounting	Wallmount	
Anti-Vibration	0.5 Grms/ 5~ 500Hz/ operation – HDD	
Anti-Shock	10 G peak acceleration (11 msec. duration)	
Environmental		
Operating temperature	32°F ~ 122°F (0°C ~ 50°C)	
Certificate	CE & FCC Class A	
Operating System		
MS Windows	Windows® 7 32/64 bit, Windows® 8.1 32/64 bit	
Linux	Fedora	

# ACS-1U01-BT4

## Dimension

Unit: mm



## Ordering Information

Part Number	CPU	RAM Module	Display	Cooler	Storage	LAN	USB	Serial Port	Expansion Slot	Power	Mounting
ACS-1U01-BT4-1900-V10	J1900 2.42G/2M	—	VGA x 1 HDMI x 1	Fanless w/ CPU heatsink	2.5" HDD shelf, Full-Size Mini-Card (mSATA) x 1	GbE x 1	USB3 x 1 USB 2.0 x 7	RS-232 x 5, RS-232/422/485 x 1	Half-size Mini-Card x 1 w/o SIM Slot	DC12V	wallmount

## Packing List

- Wallmount Kit
- 2.5" HDD tray
- Product DVD
- ACS-1U01-BT4 (1U Chassis w/ EMB-BT4)

## Optional Accessories

- **1702031802**  
Power Cord (US & Taiwan Type)
- **1702031803**  
Power Cord (European Type)
- **170203180B**  
Power Cord (China Type)
- **170203180E**  
Power Cord (Japanese Type)
- **1255300607**  
60W Power Adapter